

TECHNICAL SPECIFICATIONS

i-SENSYS MF264dw / MF267dw / MF269dw

| | | | |
|--------------------------------------|--|--|---|
| Machine type | Mono Laser All-In-One | Group dials/destinations | Max. 104 dials / Max. 50 destinations in one group |
| Available functions | MF264dw: Print, Copy and Scan MF267dw/MF269dw: Print, Copy, Scan and Fax | Sequential broadcast | Max. 114 destinations |
| PRINTER | | Memory backup | Permanent fax memory backup (Backup with flash memory) |
| Print speed | Single sided: Up to 28 ppm (A4) Double sided: Up to 17.8 ipm (A4) | Double sided faxing | Yes (Transmit and Receive) |
| Printing method | Monochrome laser beam printing | Other features | Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports |
| Print quality | Up to 1200 x 1200 dpi | MEDIA HANDLING | |
| Print resolution | 600 x 600 dpi | Scanner type | MF264dw/MF267dw: Flatbed and Automatic Document Feeder (ADF) MF269dw: Flatbed and Duplex Automatic Document Feeder (DADF) |
| Warm-up time | Approx. 15 seconds or less from power on | Paper input (Standard) | 250-sheet cassette 1-sheet multi-purpose tray |
| First Print Out Time | Approx: 5.2 seconds or less | | MF264dw/MF267dw: 35-sheet ADF MF269dw: 50-sheet DADF |
| Printer languages | UFRII-LT, PCL 5e, PCL6 | Paper input (Option) | 50-sheet |
| Fonts | 45 PCL fonts | Paper output | Plain paper, Recycled paper, Heavy Paper, Bond Paper, Label, Envelope |
| Print margins | 5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope) | Media types | Cassette : A4, A5, A5(Landscape), B5, A6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Envelop (COM10, DL, C5), Custom sizes: Min. 76.2 x 127 mm Max. 215.9 x 355.6 mm |
| Toner saver mode | Yes | Media sizes | Multi-purpose tray: A4, A5, A5(Landscape), B5, A6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COM10, Monarch, DL, C5), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm |
| Advanced printing features | Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android: Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app | Media weights | ADF: MF264dw/MF267dw: A4, A5, B5, B6, Legal, Letter, Custom sizes (W x L): Min. 105 x 148 mm Max 216 x 356 mm MF269dw: A4, A5, B5, B6, Legal, Letter, Custom sizes (W x L): Min. 127 x 140 mm Max 216 x 356 mm |
| COPIER | | Double sided printing | Automatic A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, Foolscap 60 to 105 g/m ² |
| Copy speed | Single sided: Up to 28 ppm (A4) Double sided: Up to 17.8 ipm (A4) | Interface & Software | Interface type |
| First Copy Output Time (FCOT) | Approx. 8.2 seconds or less | Interface type | USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g/n, Wireless Direct Connection |
| Copy resolution | Up to 600 x 600 dpi | Operating System compatibility | Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008 / Mac OS X version 10.8.5 & up / Mac OS 10.13 & up Linux5 |
| Copy modes | Text/Photo, Text/Photo (High speed), Photo, Text | Network Protocol | Print: LPD, RAW, WSD-Print (IPv4, IPv6), IPP, IPPS Scan: Email, SMB, WSD-Scan(IPv4, IPv6) TCP/IP Application Services: Bonjour(mDNS), DHCP, Auto IP (IPv4) DHCPv6 (IPv6), BOOTP, RARP Management: SNMPv1, SNMPv3 (IPv4, IPv6) HTTP, HTTPS, SNMP Security (wired): IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS/PPS), Security (wireless): WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(AES) |
| Double sided copying | MF264dw/MF267dw: 1-sided to 2-sided (Automatic) MF269dw: 2-sided to 2-sided (Automatic) | Software and printer management | MF Scan Utility, Remote User Interface (RUI), Toner Status Tool, |
| Multiple copy | Up to 999 copies | | |
| Reduction / Enlargement | 25-400% in 1% increments | | |
| Other features | Collate Copies, 2 on 1, 4 on 1, ID card copy | | |
| SCANNER | | | |
| Type | Colour | | |
| Scan resolution | Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi | | |
| Scan speed | MF264dw/MF267dw: Single sided mono: 20ipm (300x600dpi) Single sided colour: 15ipm (300x600dpi) MF269dw: Single sided mono: 22ipm (300x600dpi) Single sided colour: 15ipm (300x600dpi) Double sided mono: 8ipm (300x600dpi) Double sided colour: 5ipm (300x600dpi) | | |
| Colour scanning depth | 24 bit/24 bit (input/output) | | |
| Greyscales | 256 levels | | |
| Compatibility | TWAIN, WIA, ICA | | |
| Max. scan width | 215.9mm | | |
| Scan to E-mail | MF267dw/MF269dw only: TIFF/JPEG/PDF/Compact PDF | | |
| Scan to PC | TIFF/JPEG/PDF/Compact PDF/Searchable PDF ² | | |
| Scan to USB memory key | | | |
| Scan to FTP | | | |
| Scan to Cloud | TIFF/JPEG/PDF/PNG ³ | | |
| iFAX | | | |
| FAX | MF267dw/MF269dw only | | |
| Modem speed | 33.6 Kbps (Up to 3 seconds/page ³) | | |
| RECEIVE MODE | Fax only, Fax/Tel Auto Switch, Answer Mode, Manual, DRPD: Select Fax | | |
| Fax resolution | Normal: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi | | |
| FAX memory | Up to 256 pages ⁴ | | |
| Speed dials | Up to 104dials | | |

TECHNICAL SPECIFICATIONS

i-SENSYS MF264dw / MF267dw / MF269dw

GENERAL FEATURES

| | |
|-------------------------------------|---|
| Recommended Monthly Print Volume | 250 - 2,500 pages per month |
| Duty cycle | Max. 30,000 pages per month ⁶ |
| Processor Speed | 400MHz |
| Memory | 256MB |
| Control panel | MF264dw: 5 lines B&W LCD MF267dw/MF269dw: 6-line LCD B&W Touch Screen |
| "Dimensions with trays (W x D x H)" | 390 mm x 405 mm x 375 mm |
| "Installation space (W x D x H)" | MF264dw/MF267dw: 435 mm x 620 mm x 645 mm MF269dw: 429 mm x 620 mm x 670 mm |
| Weight | MF264dw/MF267dw: Approx. 12.9 Kg MF269dw: Approx. 13.8 Kg |
| Operating environment | Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) |
| Power Source | 220-240V(±10%) 50/60Hz (±2Hz) |
| Power Consumption | Maximum: Approx. 1180 W Standby: Approx. 5.7 W Sleep mode: Approx. 0.8 W Power switch off: 0.5W or less Typical Electricity Consumption (TEC): 0.8 kWh/week Idle time required to enter sleep mode: 1-30 min (default: 1 min) Idle time required to enter Auto Shutdown: 4 hours (default) http://www.canon-europe.com/For_Work/Lot26/index.aspx |
| Noise Levels | Sound Pressure ⁷ : Active: MF264dw/MF267dw: 51 dB in B/W printing MF269dw: 50 dB in B/W printing Standby: Inaudible Sound Power ⁷ : Active: 70.7 dB or less in B/W printing Standby: N/A |

CONSUMABLES

| | |
|------------|---|
| Cartridges | Cartridge 051 (1,700 pages ⁸) ⁹ Cartridge 051H (4,100 pages ⁸) ⁹ Drum Cartridge 051 (23,000 pages ⁸) ⁹ |
|------------|---|

ACCESSORIES/ OPTIONS

| | |
|-------|---|
| Items | MF267dw/MF269dw only TEL 6 KIT (Telephone handset) |
|-------|---|

Notes:

^[1]A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

^[2]Scan by MF Scan Utility

^[3]Scan by MF Scan Utility or Canon PRINT Business app

^[4]Based on ITU-T Standard Chart No. 1

^[5]Linux support both printing and scanning
Available from December 2018.

^[6]Duty cycle is defined as the maximum number of printed pages for a single peak month.
Any usage above the recommended duty cycle may decrease the life of the product.

^[7]Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

^[8]Based on ISO/IEC 19752

^[9]Printer ships with Cartridge 051 (1,700 pages), Drum Cartridge 051 (23,000 pages)